

TECHNICAL DATA SHEET - TECHSPAN 5002CS EXTRUDER WELDER

- High quality heavy duty Extruder Welder
- Integrated air supply
- Accepts 4mm or 5mm plastic welding rod
- Separate control of preheat & melt
- Tempered steel screw & barrel
- No wearing parts on rod feed system
- 3.5kg/hr with 4mm rod
- 5.8kg/hr with 5mm rod
- For welding : PE, PP
- 2 Year warranty *



Advanced & very robust design with decisively less wear points than other extruders. Cold start prevention. Patented temperature measurement. Built-in stand. Full range of welding shoes available. Adjustable handle positions. Optional rod de-reeler and full range of welding rods available.

Technical Data

Voltage	V	230
Frequency	Hz	50/60
Welding Capacity, max	kg/hr	5.8
Power Consumption, drive	kW	1.6
Power Consumption, melt	kW	1.2
Power Consumption, preheat	kW	3.4
Airflow	l/min.	300
Welding Rod	mm	4 or 5
Dimensions	mm	
Weight	kg	9.8

* Warranty does not cover heating elements or normal wearing parts.

Australia:

P O Box 1012, Mascot, NSW 1460, Sydney
Ph: 1-800 148 791 Fx: 1-800 148 799
sales@techspanonline.com

New Zealand:

P O Box 15262, New Lynn, Auckland
Ph: ++64 9 8276567 Fx: ++64 9 827 6596
sales@techspanonline.com

TECHSPAN GROUP
PLASTIC WELDING SYSTEMS

www.techspanonline.com